



#### NOTE

1. PRODUCT TO BE FREE OF DEFECTS SUCH AS FLASH, SCRATCH, WELD-LINE, SINK-MARK, TWIST, ETC.
2. LOCATIONS OF GATES, PARTING-LINE, AND EJECTOR PINS MUST BE APPROVED BY DEK R&D TEAM, PRIOR TO MOLD CONSTRUCTION.
3. PRODUCT MUST MATCH ITS COUNTERPART.
4. INTERNAL SURFACES TO BE FINISHED PER SANDING.
5. EXTERNAL SURFACE TEXTURE IS K-106.
6. OTHERWISE TOLERANCE .0=±0.10, .00=±0.05
7. ECCENTRICITY OF CENTERLINE WILL BE MAX0.02
8. TWIST OF BENT BE MAX0.05
9. FLASH WILL PERMITTED MAX0.05

部 番 PART NO.			名 稱 TITLE		材 料 MATERIAL	規 格 SPECIFICATION	處 理 TREATMENT	備 考 REMARK
					三角法 THIRD ANGLE PROJECTION	單 位 UNIT mm INCH	尺 度 SCALE 2 / 1	提出先 USER
					承認 APPROVAL	檢 圖 CHECK	設 計 DESIGN	圖 名 TITLE
								圖 番 DRAWG. NO.
MARK	DATE	APPR	CHECK	DESIGN				

